

FLOR-CLEAN™ DC

Technical Information Sheet

Polished Concrete Daily Cleaner

FLOR-CLEAN™ is a neutral pH cleaner that is pre-measured to dissolve in a 15 gallon auto-scrubber tank. When used for cleaning an ULTRAFLOOR® surface or other polished concrete surfaces, the material will provide additional luster during normal cleaning cycles. This material will not harm the exposed concrete flooring finish or any surrounding surfaces.

Limitations

KEEP FROM FREEZING. DO NOT HEAT. STORE BETWEEN 36°F (2°C) and 100°F (38°C). Do not apply when air, material and surface temperatures are expected to be outside these parameters.

Coverage Rate

Dilute FLOR-CLEAN DC in an auto-scrubber tank at the rate of 1-5% by volume.

Equipment

FLOR-CLEAN™ will work with any typical auto-scrubber or self applying floor cleaning equipment. The auto-scrubber should be equipped with a soft burnishing pad or a FLOR-GRIT™ diamond impregnated pad while using the FLOR-CLEAN™. Never use nylon grit brushes for cleaning polished concrete floors. Not designed for use in a mop bucket.

Packaging & Shelf Life

The FLOR-CLEAN™ DC comes in 1 gallon plastic containers. The shelf life when stored properly indoors is 1 year.

USA HEADQUARTERS
DIAMATIC USA

5220 Gaines Street
San Diego, CA 92110

Toll free: 866.295.5512

Tel: 619.295.0893

Fax: 619.295.0754

Email: info@diamaticusa.com

www.diamaticusa.com

www.ultraflor.com

NORTHEAST FACILITY
DIAMATIC USA

622 Grant Road
Folcroft, PA 19032

Toll free: 866.295.5512 EX: 1009

Fax: 888.283.3312

Email: info@diamaticusa.com

Application

The application temperature range should be between 40-90 degrees F (5-32 C).

Add the FLOR-CLEAN™ DC to the water in an auto-scrubbing machine at the rate 1-5% by volume. Operate the machine as in a normal cleaning cycle. No special requirements necessary.

The auto-scrubber should be fitted with a soft pad or FLOR-GRIT™ diamond impregnated pad for cleaning and burnishing. Never use a nylon grit brush as they dull the surface or strip the guard product installed to protect the floor from staining.

Safety

This product is non-toxic and non-hazardous. However care should be taken to prevent children from coming into contact with any chemicals. For eye contact, flush with running water for 15 minutes. For ingestion, give milk, water or any non-alcoholic liquid. KEEP OUT OF REACH OF CHILDREN. Refer to the SDS sheet for complete first aid and safety information.



**WARNING
IRRITANT**

Technical Data

- 1 HEALTH
- 0 FIRE
- 0 REACTIVITY
- C PERSONAL PROTECTION
- X IRRITANT
- ✓ VOC 90 < gms/L


nanoLithium
Patented Technologies by Advan
Nano-Lithium® (NL)
Concrete Treatment
www.nano-lithium.com